

Switch D-Link DGS-1210-08P 8 p 10 / 100 / 1000 Mbps 2 x SFP



Si eres un apasionado de la informática y la electrónica, te gusta estar a la última en tecnología y no perderte detalle, compra Switch D-Link DGS-1210-08P 8 p 10 / 100 / 1000 Mbps 2 x SFP al...

Calificación: Sin calificación

Precio

Precio con descuento 181,61 €

Precio de venta 219,75 €

Precio de venta sin impuestos 181,61 €

24 h



[Haga una pregunta sobre este producto](#)

Descripción Si eres un apasionado de la **informática y la electrónica**, te gusta estar a la última en tecnología y no perderte detalle, compra **Switch D-Link DGS-1210-08P 8 p 10 / 100 / 1000 Mbps 2 x SFP** al mejor precio.

Marca	D-Link
Modelo	DGS-1210-08P
Especificaciones	<ul style="list-style-type: none">- 8 puertos 10/100/1000 Mbps- 2 Puertos SFP <p>Standards:</p> <ul style="list-style-type: none">- IEEE 802.3 compliant- IEEE 802.3u compliant- IEEE 802.3ab compliance- Supports Half-Full-duplex operation at 10/100Mbps- Supports Full-duplex operation at 1000Mbps- Supports Auto-Negotiation for each port- Auto MDI/MDIX- IEEE 802.3x Flow Control support- IEEE 802.3az compliant

Rendimiento:

- 20Gbps
- Max.velocidad envío
- 14.9 Mpps

- Tamaño tabla MAC
16K Entries
- Packet Buffer
6Mbits
- Jumbo Frame
Hasta 13,000 Bytes
- **Alimentación:**
110 to 240 VAC, 50/60HZ internal universal power supply
- Max.Consumo
60 Watts
- Consumo Standby
5.6 Watts
- Sin ventilador
- Nivel acústico:
0 dBA
- Dimensions (W x D x H)
280 x 180 x 44 mm
- 19-inch standard rack
1U
- Peso:
0.42kg
- LEDs
Power (per device)
Link/Activity/Speed/PoE (per 10/100/1000 Mbps port)
Link/Activity/Speed (per SFP port)
Button to switch LED display mode between PoE and Link/ActivityPower (per device)
- Certifications
CE Class A
cUL, LVD
- MTBF
503,585 Hours (DGS-1100-08)

Funciones L2

- MAC Address Table: 16K
- Flow Control
802.3x Flow Control
HOL Blocking Prevention
- Jumbo Frame up to 13,000 Bytes
- IGMP Snooping
IGMP v1/v2 Snooping
IGMP Snooping v3 Awareness
Supports 256 IGMP groups
Supports at least 64 static multicast addresses
IGMP per VLAN
Supports IGMP Snooping Querier
- MLD Snooping1
Supports MLD v1/v2 awareness
Supports 256 groups
Fast Leave
- Spanning Tree Protocol
802.1D STP
802.1w RSTP
- Loopback Detection
- 802.3ad Link Aggregation
DGS-1210-10P: Max. 5 groups per device/8 ports per group
DGS-1210-20: Max. 10 groups per device/8 ports per group
DGS-1210-28/28P: Max. 14 groups per device/8 ports per group
DGS-1210-52: Max. 26 groups per device/8 ports per group
DGS-1210-16/24/48: Max. 8 groups per device/8 ports per group
- Port Mirroring
One-to-One, Many-to-One
Supports Mirroring for Tx/Rx/Both
- Multicast Filtering
Forwards all unregistered groups
Filters all unregistered groups
LLDP, LLDP-MED
- VLAN**
- 802.1Q Tagged VLAN

- VLAN Group
 - Max. 256 static VLAN groups
 - Max. 4094 VIDs
- Management VLAN
- Asymmetric VLAN
- Auto Voice VLAN
 - Max. 10 user-defined OUI
 - Max. 8 default OUI
- Auto Surveillance VLAN
- Quality of Service (QoS)**
- 802.1p Quality of Service
- Queue Handling
 - Strict
 - Weighted Round Robin (WRR)
- 8 queues per port
- Bandwidth Control
 - Port-based (Ingress/Egress, min. granularity for 10/100/1000Base-T ports is 15 Kb/s)
- CoS based on
 - 802.1p Priority Queues
 - DSCP
 - ToS
 - TCP/UDP port number
 - IPv6 traffic class1
- Access Control List (ACL)**
- Max. 50 profiles
- Max. 200 rules shared by profiles
- Single or multiple ports (each rule)
- ACL based on
 - MAC Address
 - IPv4 Address (ICMP/IGMP/TCP/UDP)
 - IPv6 Address (ICMP/TCP/UDP)1
 - 802.1p
 - DSCP
 - Ether type
 - IPv6 traffic class1
- ACL Actions
 - Permit
 - Deny
- Seguridad**
- Port Security
 - Supports up to 64 MAC addresses per port
- Broadcast/Multicast/Unicast Storm Control
- Static MAC
- D-Link Safeguard Engine
- DHCP Server Screening
- Trusted Host
- ARP Spoofing Prevention
 - Max. 64 entries
- SSL
 - Supports v1/v2/v3
 - Supports IPv4/IPv6
- Traffic Segmentation
- Smart Binding1
 - Discover connected devices and click to bind
 - ARP Packet Inspection: 512 entries
 - IP Packet Inspection: 128 entries
 - Supports DHCP Snooping
- AAA**
- 802.1X Port-based Authentication
 - Supports RADIUS Server
 - Supports EAP, OTP, TLS, TTLS, PEAP
- OAM**
- Cable Diagnostics
- Factory Reset
- MIB**
- 1213 MIB II
- 1493 Bridge MIB
- 1907 SNMP v2 MIB
- 1215 Trap Convention MIB

- 2233 Interface Group MIB
- D-Link Private MIB
- Power-Ethernet MIB
- LLDP MIB
- D-Link ZoneDefense MIB1
- RFC Standard Compliance**
- RFC 783 TFTP
- RFC 854 Telnet Server
- RFC 951 BootP/DHCP Client
- RFC 1157 SNMP v1, v2, v3
- RFC 1213 MIB II, IF MIB
- RFC 1215 MIB Traps Convention
- RFC 1350 TFTP
- RFC 1493 Bridge MIB
- RFC 1542 BootP/DHCP Client
- RFC 1769 SNTTP
- RFC 1901 SNMP v1, v2, v3
- RFC 1907 SNMP v2 MIB
- RFC 1908 SNMP v1, v2, v3
- RFC 2068 FCS
- RFC 2131 BootP/DHCP Client
- RFC 2138 RADIUS Authentication
- RFC 2139 RADIUS Authentication
- RFC 2233 Interface Group MIB
- RFC 2246 SSL
- RFC 2475
- RFC 2570 SNMP v1, v2, v3
- RFC 2575 SNMP v1, v2, v3
- RFC 2598 CoS
- RFC 2616 FCS
- RFC 2618 RADIUS Authentication
- RFC 2819 RMON v1
- RFC 2865 RADIUS Authentication
- RFC 3164 System Log
- RFC 3195 System Log
- RFC 3411-17 SNMP
- RFC 3621 Power Ethernet MIB
- Gestión**
- Multi-Language Web-based GUI
 - English (default)
 - Simplified Chinese1
 - Traditional Chinese1
 - French1
 - German1
 - Italian1
 - Japanese1
 - Portuguese1
 - Russian1
 - Spanish1
- SmartConsole Utility2
- Simplified CLI
- Telnet Server
- TFTP Client
- IPv6 Neighbor Discovery
- Configurable MDI/MDIX
- SNMP
 - Supports v1, v2, v3
- SNMP Trap
- System Log
 - Max. 500 log entries
- BootP/DHCP Client
- D-Link Network Assistant support1
- SNTTP
- ICMPv6
- IPv4/v6 Dual Stack1
- DHCP Auto Configuration
- RMON v1
- D-Link Green 3.0 Technology**
- Power Saving by:

Link Status
 Cable Length detection
 LED or Port Shutoff
 Port Standby mode
 System Hibernation mode
 Time-based PoE (PoE model only)

Fecha de revisión

03-04-2014 por FE4

- Marca: D-Link
- Modelo: DGS-1210-08P
- Especificaciones:
 - 8 puertos 10/100/1000 Mbps
 - 2 Puertos SFP Standards
 - IEEE 802.3 compliant
 - IEEE 802.3u compliant
 - IEEE 802.3ab compliance
 - Soporta Half/Full-duplex operation at 10/100Mbps
 - Soporta Full-duplex operation at 1000Mbps
 - Soporta Auto-Negotiation for each port
 - Auto MDI/MDIX
 - IEEE 802.3x Flow Control support
 - IEEE 802.3az compliant Rendimiento: 20Gbps
 - Max.velocidad envío 14.9 Mpps
 - Tamaño tabla MAC 16K Entries
 - Packet Buffer 6Mbits
 - Jumbo Frame Hasta 13,000 Bytes
 - Alimentación: 110 to 240 VAC, 50/60HZ internal universal power supply
 - Max.Consumo 60 Watts
 - Consumo Standby 5.6 Watts
 - Sin ventilador
 - Nivel acústico: 0 dBA
 - Dimensions (W x D x H) 280 x 180 x 44 mm 19-inch standard rack 1U
 - Peso: 0.42kg
 - LEDs Power (per device) Link/Activity/Speed/PoE (per 10/100/1000 Mbps port) Link/Activity/Speed (per SFP port) Button to switch LED display mode between PoE and Link/ActivityPower (per device)
 - Certifications CE Class A cUL, LVD
 - MTBF 503,585 Hours (DGS-1100-08)Funciones L2
 - MAC Address Table: 16K
 - Flow Control 802.3x Flow Control HOL Blocking Prevention
 - Jumbo Frame up to 13,000 Bytes
 - IGMP Snooping IGMP v1/v2 Snooping IGMP Snooping v3 Awareness Supports 256 IGMP groups Supports at least 64 static multicast addresses IGMP per VLAN Supports IGMP Snooping Querier
 - MLD Snooping1 Supports MLD v1/v2 awareness Supports 256 groups Fast Leave
 - Spanning Tree Protocol 802.1D STP 802.1w RSTP
 - Loopback Detection
 - 802.3ad Link Aggregation DGS-1210-10P: Max. 5 groups per device/8 ports per group DGS-1210-20: Max. 10 groups per device/8 ports per group DGS-1210-28/28P: Max. 14 groups per device/8 ports per group DGS-1210-52: Max. 26 groups per device/8 ports per group DGS-1210-16/24/48: Max. 8 groups per device/8 ports per group
 - Port Mirroring One-to-One, Many-to-One Supports Mirroring for Tx/Rx/Both
 - Multicast Filtering Forwards all unregistered groups Filters all unregistered groups LLDP, LLDP-MEDVLAN
 - 802.1Q Tagged VLAN
 - VLAN Group Max. 256 static VLAN groups Max. 4094 VIDs
 - Management VLAN
 - Asymmetric VLAN
 - Auto Voice VLAN Max. 10 user-defined OUI Max. 8 default OUI
 - Auto Surveillance VLANQuality of Service (QoS)
 - 802.1p Quality of Service
 - Queue Handling Strict Weighted Round Robin (WRR)
 - 8 queues per port
 - Bandwidth Control Port-based (Ingress/Egress, min. granularity for 10/100/1000Base-T ports is 15 Kb/s)
 - CoS based on 802.1p Priority Queues DSCP ToS TCP/UDP port number IPv6 traffic class1Access Control List (ACL)
 - Max. 50 profiles
 - Max. 200 rules shared by profiles
 - Single or multiple ports (each rule)
 - ACL based on MAC Address IPv4 Address (ICMP/IGMP/TCP/UDP) IPv6 Address (ICMP/TCP/UDP)1 802.1p DSCP Ether type IPv6 traffic class1
 - ACL Actions Permit DenySeguridad
 - Port Security Supports up to 64 MAC addresses per port

- Broadcast/Multicast/Unicast Storm Control
- Static MAC
- D-Link Safeguard Engine
- DHCP Server Screening
- Trusted Host
- ARP Spoofing Prevention Max. 64 entries
- SSL Supports v1/v2/v3 Supports IPv4/IPv6
- Traffic Segmentation
- Smart Binding1 Discover connected devices and click to bind ARP Packet Inspection: 512 entries IP Packet Inspection: 128 entries Supports DHCP SnoopingAAA
- 802.1X Port-based Authentication Supports RADIUS Server Supports EAP, OTP, TLS, TTLS, PEAP/POAM
- Cable Diagnostics
- Factory ResetMIB
- 1213 MIB II
- 1493 Bridge MIB
- 1907 SNMP v2 MIB
- 1215 Trap Convention MIB
- 2233 Interface Group MIB
- D-Link Private MIB
- Power-Ethernet MIB
- LLDP MIB
- D-Link ZoneDefense MIB1RFC Standard Compliance
- RFC 783 TFTP
- RFC 854 Telnet Server
- RFC 951 BootP/DHCP Client
- RFC 1157 SNMP v1, v2, v3
- RFC 1213 MIB II, IF MIB
- RFC 1215 MIB Traps Convention
- RFC 1350 TFTP
- RFC 1493 Bridge MIB
- RFC 1542 BootP/DHCP Client
- RFC 1769 SNTP
- RFC 1901 SNMP v1, v2, v3
- RFC 1907 SNMP v2 MIB
- RFC 1908 SNMP v1, v2, v3
- RFC 2068 FCS
- RFC 2131 BootP/DHCP Client
- RFC 2138 RADIUS Authentication
- RFC 2139 RADIUS Authentication
- RFC 2233 Interface Group MIB
- RFC 2246 SSL
- RFC 2475
- RFC 2570 SNMP v1, v2, v3
- RFC 2575 SNMP v1, v2, v3
- RFC 2598 CoS
- RFC 2616 FCS
- RFC 2618 RADIUS Authentication
- RFC 2819 RMON v1
- RFC 2865 RADIUS Authentication
- RFC 3164 System Log
- RFC 3195 System Log
- RFC 3411-17 SNMP
- RFC 3621 Power Ethernet MIBGestión
- Multi-Language Web-based GUI English (default) Simplified Chinese1 Traditional Chinese1 French1 German1 Italian1 Japanese1 Portuguese1 Russian1 Spanish1
- SmartConsole Utility2
- Simplified CLI
- Telnet Server
- TFTP Client
- IPv6 Neighbor Discovery
- Configurable MDI/MDIX
- SNMP Supports v1, v2, v3
- SNMP Trap
- System Log Max. 500 log entries
- BootP/DHCP Client
- D-Link Network Assistant support1
- SNTP
- ICMPv6
- IPv4/v6 Dual Stack1

- DHCP Auto Configuration
- RMON v1D-Link Green 3.0 Technology
- Power Saving by: Link Status Cable Length detection LED or Port Shutoff Port Standby mode System Hibernation mode Time-based PoE (PoE model only)
- Fecha de revisión: 03-04-2014 por FE4

Comentarios

Aún no hay comentarios para este producto.