

Cámara IP D-Link DCS-2330L HD IR Micro SD / SDHC Wifi



Si eres un apasionado de la informática y la electrónica, te gusta estar a la última en tecnología y no perderte detalle, compra Cámara IP D-Link DCS-2330L HD IR Micro SD / SDHC Wifi al mejor...

Calificación: Sin calificación

Precio

Precio con descuento 208,74 €

Precio de venta 252,58 €

Precio de venta sin impuestos 208,74 €

[Haga una pregunta sobre este producto](#)

Descripción Si eres un apasionado de la **informática y la electrónica**, te gusta estar a la última en tecnología y no perderte detalle, compra **Cámara IP D-Link DCS-2330L HD IR Micro SD / SDHC Wifi** al mejor precio.

Marca	D-Link
Modelo	DCS-2330L
Interfaces	- 802.11n wireless - 10/100 Fast Ethernet port - MicroSD/SDHC card slot para almacenamiento interno - 16GB MicroSD card incluida, soporta grabación hasta 7 días
Imagen	- HD resolution (1280 x 720) - H.264 and Motion JPEG compression - ePTZ viewing - Simultaneous multi-stream support - Privacy Mask feature - Supports multiple access lists
Características	Cámara - Sensor 1/4" Megapixel progressive CMOS - Distancia IR: 5 m. - Iluminación Mínima: 0 lux con IR LED - Built-in Infrared-Cut Removable (ICR) Filter module - Built-in PIR sensor (5 metre) - Micrófono - 10x digital zoom - Focal length: 3.45 mm - Aperture: F2.0 - Exposure time: 1/7.5 to 1/10,000 sec. - Minimum object distance: 500 mm - Angulo de visión: (H) 57.8° (V) 37.8° (D) 66° Carcasa - IP65 compliant weatherproof housing Funcionalidades imagen - Configurable image size, quality, frame rate, and bitrate - Time stamp and text overlays - Configurable motion detection windows - Configurable privacy mask zones - Configurable shutter speed, brightness, saturation, contrast, and sharpness Video-Compresión - Simultaneous H.264/MJPEG format compression - H.264 multicast streaming - JPEG for still images Video-Resolución - 16:9 - 1280x720, 800x448,640x360, 480x272, 320x176 up to 30 fps recording1 - 4:3 - 960x720, 800x592, 640x480, 480x352, 320x240 up to 30 fps recording1 Audio - AAC - G.71 Protocolos red - IPv6 - IPv4 - TCP/IP - UDP - ICMP - DHCP client - NTP client (D-Link) - DNS client - DDNS client (D-Link) - SMTP client - FTP client - HTTP / HTTPS - Samba client

- PPPoE
- UPnP port forwarding
- RTP / RTSP / RTCP
- IP filtering
- QoS
- CoS
- Multicast
- IGMP
- ONVIF compliant

Seguridad

- Administrator and user group protection
- Password authentication
- HTTP and RTSP authentication

Requisitos acceso web

- Browser: Internet Explorer, Firefox, Chrome

Gestión de eventos

- Motion detection
- Event notification and uploading of snapshots/video clips via e-mail or FTP
- Supports multiple SMTP and FTP servers
- Multiple event notifications
- Multiple recording methods for easy backup

Gestión remota

- Take snapshots/video clips and save to local hard drive
- Configuration interface accessible via web browser

Mobile Support

- Windows 8/7/Vista/XP, Pocket PC, tablet, or mobile phone-
- mydlink™ mobile app for iOS and Android mobile devices

D-Viewcam™ System Requirements

- Operating System: Microsoft Windows 8/7/Vista/XP
- Web Browser: Internet Explorer 7 or higher Protocol: Standard TCP/IP

D-Viewcam™ Software Functions

- Viewing of up to 32 cameras on one screen
- Scheduled motion triggered, or manual recording options
- Supports all management functions in web interface
- Remote management/control of up to 32 cameras

Otras características

Dimensiones

- 105 x 66 x 45.7 mm

Peso

- 134 g ± 5%

Alimentación

- Output: 5 V DC, 1.2 A
- Input: 100 to 240 V AC, 50/60 Hz

Consumo

- 5 watts max. - -

Temperatura

- Operating: -25 to 45 °C (-13 to 113 °F)
- Storage: -20 to 70 °C (-4 to 158 °F)

Humedad

- Operating: 20% to 80% non-condensing
- Storage: 5% to 95% non-condensing

Certificaciones

- CE
- FCC class B
- C-Tick
- IC

11-11-2014 por FE4

Fecha de revisión

- Marca: D-Link
- Modelo: DCS-2330L
- Interfaces :
 - 802.11n wireless
 - 10/100 Fast Ethernet port
 - MicroSD/SDHC card slot para almacenamiento interno
 - 16GB MicroSD card incluida, soporta grabación hasta 7 días
- Imagen:

- HD resolution (1280 x 720)
- H.264 and Motion JPEG compression
- ePTZ viewing
- Simultaneous multi-stream support
- Privacy Mask feature
- Supports multiple access lists
- Características:
 - Cámara
 - Sensor 1/4" Megapixel progressive CMOS
 - Distancia IR: 5 m.
 - Iluminación Mínima: 0 lux con IR LED
 - Built-in Infrared-Cut Removable (ICR) Filter module
 - Built-in PIR sensor (5 metre)
 - Micrófono
 - 10x digital zoom
 - Focal length: 3.45 mm
 - Aperture: F2.0
 - Exposure time: 1/7.5 to 1/10,000 sec.
 - Minimum object distance: 500 mm
 - Angulo de visión: (H) 57.8° (V) 37.8° (D) 66°
 - IP65 compliant weatherproof housing
 - Configurable image size, quality, frame rate, and bitrate
 - Time stamp and text overlays
 - Configurable motion detection windows
 - Configurable privacy mask zones
 - Configurable shutter speed, brightness, saturation, contrast, and sharpness
 - Simultaneous H.264/MJPEG format compression
 - H.264 multicast streaming
 - JPEG for still images
 - 16:9
 - 1280x720, 800x448, 640x360, 480x272, 320x176 up to 30 fps recording
 - 4:3
 - 960x720, 800x592, 640x480, 480x352, 320x240 up to 30 fps recording
 - AAC
 - G.711
 - IPv6
 - IPv4
 - TCP/IP
 - UDP
 - ICMP
 - DHCP client
 - NTP client (D-Link)
 - DNS client
 - DDNS client (D-Link)
 - SMTP client
 - FTP client
 - HTTP / HTTPS
 - Samba client
 - PPPoE
 - UPnP port forwarding
 - RTP / RTSP / RTCP
 - IP filtering
 - QoS
 - CoS
 - Multicast
 - IGMP
 - ONVIF compliant
 - Administrator and user group protection
 - Password authentication
 - HTTP and RTSP authentication
 - Browser: Internet Explorer, Firefox, Chrome
 - Motion detection
 - Event notification and uploading of snapshots/video clips via e-mail or FTP
 - Supports multiple SMTP and FTP servers
 - Multiple event notifications
 - Multiple recording methods for easy backup
 - Take snapshots/video clips and save to local hard drive
 - Configuration interface accessible via web browser
 - Windows 8/7/Vista/XP, Pocket PC, tablet, or mobile phone-

- mydlink™ mobile app for iOS and Android mobile devices D-Viewcam™ System Requirements
- Operating System: Microsoft Windows 8/7/Vista/XP
- Web Browser: Internet Explorer 7 or higher Protocol: Standard TCP/IP D-Viewcam™ Software Functions
- Viewing of up to 32 cameras on one screen
- Scheduled motion triggered, or manual recording options
- Supports all management functions in web interface
- Remote management/control of up to 32 cameras
- Otras características:
 - Dimensiones
 - 105 x 66 x 45.7 mm Peso
 - 134 g ± 5% Alimentación
 - Output: 5 V DC, 1.2 A
 - Input: 100 to 240 V AC, 50/60 Hz Consumo
 - 5 watts max.
 - - Temperatura
 - Operating: -25 to 45 °C (-13 to 113 °F)
 - Storage: -20 to 70 °C (-4 to 158 °F) Humedad
 - Operating: 20% to 80% non-condensing
 - Storage: 5% to 95% non-condensing Certificaciones
 - CE
 - FCC class B
 - C-Tick
 - IC
- Fecha de revisión: 11-11-2014 por FE4

Comentarios

Aún no hay comentarios para este producto.