

Placa Base con CPU Integrada ASRock 90-MXGUK0-A0UA



Si eres un apasionado de la informática y la electrónica, te gusta estar a la última en tecnología y no perderte detalle, compra Placa Base con CPU Integrada ASRock 90-MXGUK0-A0UA al mejor...

Calificación: Sin calificación

Precio

Precio con descuento57,14 €

Precio de venta69,14 €

Precio de venta sin impuestos57,14 €

24 h

[Haga una pregunta sobre este producto](#)

Descripción Si eres un apasionado de la **informática y la electrónica**, te gusta estar a la última en tecnología y no perderte detalle, compra **Placa Base con CPU Integrada ASRock 90-MXGUK0-A0UA** al mejor precio.

Marca	Asrock
Modelo	D1800M
Plataforma	(90-MXGUK0-A0UA/V2) - Formato m-ATX
Chipset	- Intel® H81 Express
CPU Soportados	- Intel® Dual-Core Processor 3180M (2.41 GHz)
Memoria	(Integrado) Dual Channel DDR3/DOR3L Memory Technology - 2 x DDR3/DOR3L DIMM Slots - Supports DDR3/DOR3L 1333/1066 non-ECC, un-buffered memory - Max. capacity of system memory: 32GB
Slots Expansión	- 1 x PCI Express 2.0 x16 Slot (PCI-E2 @ x1 mode) - 2 x PCI Express 2.0 x1 Slots

Gráficos	- Intel® 7th generation (Gen 7) graphics - DirectX 11.0, Pixel Shader 5.0 - Three graphics output options: D-Sub, DVI-D and HDMI - Soporta HDMI Technology with max. resolution up to 1920x1200 @ 60Hz - Soporta DVI-D max. 1920x1200 @ 60Hz - Soporta D-Sub max. 1920x1200 @ 60Hz - Soporta Auto Lip Sync, Deep Color (12bpc), xvYCC and HBR (High Bit Rate Audio) with HDMI Port (Compliant HDMI monitor is required) - Soporta HDCP with DVI-D and HDMI Ports - Soporta Full HD 1080p Blu-ray (BD) playback with DVI-D and HDMI Ports
Puertos E/S, Conectores	E/S panel trasero: - 1 x PS/2 Keyboard - 1 x D-Sub - 2 x DVI-D - 1 x HDMI - 3 x USB 2.0 (Soporta ESD Protection (ASRock Full Spike Protection)) - 1 x USB 3.0 (Soporta ESD Protection (ASRock Full Spike Protection)) - 1 x RJ-45 LAN Port with LED (ACT/LINK LED and SPEED LED) - HD Audio Jacks: Line in / Front Speaker / Microphone E/S Internos: - 2 x Print Port - 1 x COM Port - 1 x TPM - 1 x Chassis Intrusion - 1 x CPU Fan (3 pin) - 1 x Chassis Fan (3 pin) - 1 x 24 pin ATX Power - 1 x Front Panel Audio - 2 x USB 2.0 (Support 3 USB 2.0 ports) (Soporta ESD Protection (ASRock Full Spike Protection))
Otras Características	Audio - 5.1 CH HD Audio (Realtek ALC662 Audio Codec) - Soporta Surge Protection (ASRock Full Spike Protection) LAN - PCIe x1 Gigabit LAN 10/100/1000 Mbps - Realtek RTL8111GR - Soporta Wake-On-LAN - Soporta Wake-On-LAN - Soporta Lightning/ESD Protection (ASRock Full Spike Protection) - Soporta LAN Cable Detection - Soporta Energy Efficient Ethernet 802.3az - Soporta PXE SATA - 2 x SATA2 3.0 Gb/s Connectors, support NCQ, AHCI and Hot Plug Certificaciones - FCC, CE, WHQL - EPEAT ready (EPEAT ready power supply is required)
Fecha Revisión	18-06-2014 por FE4

- Marca: ASRock
- Procesador: Integrado
- Encapsulado: LGA1150
- Memoria: DDR3
- Formato: Micro-ATX
- Almacenamiento: SATA 3
- T. Gráfica: Requiere CPU con gráficos
- Otros:
 - USB 3.0
 - HDMI
 - DVI
 - VGA Sub-D
- Marca: Asrock
- Modelo: D1800M (90-MXGUK0-A0UAYZ)
- Plataforma:
 - Formato m-ATX
- Chipset:
 - Intel® H81 Express
- CPU Soportados:
 - Intel® Dual-Core Processor J1800 (2.41 GHz) (integrado)
- Memoria :
 - Dual Channel DDR3/DDR3L Memory Technology
 - 2 x DDR3/DDR3L DIMM Slots
 - Supports DDR3/DDR3L 1333/1066 non-ECC, un-buffered memory
 - Max. capacity of system memory: 16GB*
- Slots Expansión :
 - 1 x PCI Express 2.0 x16 Slot (PCIe2 @ x1 mode)
 - 2 x PCI Express 2.0 x1 Slots
- Gráficos:
 - Intel® 7th generation (Gen 7) graphics
 - DirectX 11.0, Pixel Shader 5.0
 - Three graphics output options: D-Sub, DVI-D and HDMI
 - Soporta HDMI Technology with max. resolution up to 1920x1200 @ 60Hz
 - Soporta DVI-D max. 1920x1200 @ 60Hz
 - Soporta D-Sub max. 1920x1200 @ 60Hz
 - Soporta Auto Lip Sync, Deep Color (12bpc), xvYCC and HBR (High Bit Rate Audio) with HDMI Port (Compliant HDMI monitor is required)
 - Soporta HDCP with DVI-D and HDMI Ports
 - Soporta Full HD 1080p Blu-ray (BD) playback with DVI-D and HDMI Ports
- Puertos E/S, Conectores:
 - E/S panel trasero:
 - 1 x PS/2 Keyboard
 - 1 x D-Sub
 - 1 x DVI-D
 - 1 x HDMI
 - 3 x USB 2.0 (Soporta ESD Protection (ASRock Full Spike Protection))
 - 1 x USB 3.0 (Soporta ESD Protection (ASRock Full Spike Protection))
 - 1 x RJ-45 LAN Port with LED (ACT/LINK LED and SPEED LED)

- HD Audio Jacks: Line in / Front Speaker / Microphone E/S Internos:
- 1 x Print Port
- 1 x COM Port
- 1 x TPM
- 1 x Chassis Intrusion
- 1 x CPU Fan (3-pin)
- 1 x Chassis Fan (3-pin)
- 1 x 24 pin ATX Power
- 1 x Front Panel Audio
- 2 x USB 2.0 (Support 3 USB 2.0 ports) (Soporta ESD Protection (ASRock Full Spike Protection))
- Otras Características:
 - Audio
 - 5.1 CH HD Audio (Realtek ALC662 Audio Codec)
 - Soporta Surge Protection (ASRock Full Spike Protection) LAN
 - PCIE x1 Gigabit LAN 10/100/1000 Mb/s
 - Realtek RTL8111GR
 - Soporta Wake-On-WAN
 - Soporta Wake-On-LAN
 - Soporta Lightning/ESD Protection (ASRock Full Spike Protection)
 - Soporta LAN Cable Detection
 - Soporta Energy Efficient Ethernet 802.3az
 - Soporta PXE SATA
 - 2 x SATA2 3.0 Gb/s Connectors, support NCQ, AHCI and Hot Plug Certificaciones
 - FCC, CE, WHQL
 - ErP/EuP ready (ErP/EuP ready power supply is required)
- Fecha Revisión: 18-06-2014 por FE4

Comentarios

Aún no hay comentarios para este producto.