


Placa Base MSI 970A-G43 ATX AM3+



Si eres un apasionado de la informática y la electrónica, te gusta estar a la última en tecnología y no perderte detalle, compra Placa Base MSI 970A-G43 ATX AM3+ al mejor...

Calificación: Sin calificación

Precio

Precio con descuento65,42 €

Precio de venta79,16 €

Precio de venta sin impuestos65,42 €

24 h

[Haga una pregunta sobre este producto](#)

Descripción Si eres un apasionado de la **informática y la electrónica**, te gusta estar a la última en tecnología y no perderte detalle, compra **Placa Base MSI 970A-G43 ATX AM3+** al mejor precio.

Marca	MSI
Modelo	B75A-G41
Plataforma	- ATX Form Factor 30.5cm(L) x 22.5cm(W)
Chipset	- AMD® 970 and SB950 Chipset
CPU Soportados	- AMD® FX, Phenom II X6/X4/X3/X2, Athlon II X4/X3/X2 and Sempron CPU in AM3 / AM3+ package.

Memoria	- Soporta 4 DIMM of 1.5 Volt DDR3 1066/1333/1600/1866/2133* (OC) DRAM, 32GB Max
Slots Expansión	- Soporta modo Dual channel (2 dimms por canal) - 2 x PCI Express 2.0 x16 slots - PCI_E2 supports up to PCIe x16 speed - PCI_E4 supports up to PCIe x4 speed - 2 PCI Express 2.0 x1 slots - 2 PCI slots, support 3.3V/ 5V PCI bus Interface.
Gráficos	- Requiere CPU con gráficos.
Puertos E/S, Conectores	On-Board SATA - 6 x SATA 6Gb/s ports by AMD® SB950 - Supports storage and data transfers at up to 6Gb/s RAID Function - SATA III 1-4 support RAID 0/1/5/10 mode by AMD® SB950 USB 3.0 - 2x USB 3.0 rear I/O ports & 1x USB 3.0 onboard connector by RENESAS UPD720202 Conexiones internas - 1 x ATX 24 pin power connector - 1 x ATX 8-pin 12V CPU power connector - CPU x 1 / System x 2 FAN connectors - 1 x Front panel audio connector - 1 x Front panel connector - 1 x Chassis intrusion switch connector - 3 x USB 2.0 connectors - 1 x USB 3.0 connector - 1 x Serial connector - 1 x Clear CMOS jumper - 6 x SATA 6Gb/s connectors - 1 x TPM module connector Panel trasero: - 1 x PS/2 Keyboard - 1 x PS/2 Mouse port - 6 x USB 2.0 ports - 2 x USB 3.0 ports (blue) - 1 x LAN jack - 1 x 6 in 1 audio jack
Otras Características	Audio - Chipset integrated HD audio codecby Realtek® ALC887 - Flexible 8 channel audio with jack sensing - Compliant with Audible 1.0 Spec. LAN - Realtek® PCIe GbLAN controller 8111E - Integrated Fast Ethernet MAC and PHY in single chip - Supports 10Mbps, 100Mbps and 1000Mbps - Compliance with PCI Express Bus specification v1.0a
Fecha Revisión	27-Q2-2013 por DAV

Comentarios

Aún no hay comentarios para este producto.