

Switch de Armario D-Link DGS-1210-52P 52 Puertos RJ45 104 Gbit/s



Si eres un apasionado de la informática y la electrónica, te gusta estar a la última en tecnología y no perderte detalle, compra Switch de Armario D-Link DGS-1210-52P 52 Puertos RJ45 104 Gbit/s...

Calificación: Sin calificación

Precio

Precio con descuento848,00 €

Precio de venta1026,08 €

Precio de venta sin impuestos848,00 €

24 h
★★★★★

[Haga una pregunta sobre este producto](#)

Descripción Si eres un apasionado de la **informática y la electrónica**, te gusta estar a la última en tecnología y no perderte detalle, compra **Switch de Armario D-Link DGS-1210-52P 52 Puertos RJ45 104 Gbit/s** al mejor precio.

Marca
Modelo
Interfaz

Rendimiento

Características

DLink
DGS-1210-52P
- 48 x Puertos 10/100/1000BASE-TX
- 4 x Puertos SFP
PoE (Standard(s) / Puertos/ Potencia máx.)
- (802.3af/802.3at / 24 puertos / 193W)
- Capacidad del switch: 104 Gbps
- 64-Byte Packet Forwarding Rate: 77.4 Mpps
- MAC Address Table Size: 16K
- Packet Buffer: 3 MB por dispositivo
- Jumbo Frame: hasta 9,216 Bytes
Funcionalidades L2
- MAC Address Table: 16K entries
- IGMP Snooping:

IGMP v1/v2 Snooping
Supports 256 IGMP groups
Supports at least 64 static multicast addresses
IGMP per VLAN
Supports IGMP Snooping Querier
- Loopback Detection
- 802.3ad Link Aggregation:
Maximum of 26 groups/8 ports per group
- LLDP
- LLDP-MED
- Jumbo Frame: Up to 9,216 bytes
- Spanning Tree Protocol: 802.1D STP
802.1w RSTP
- Flow Control: 802.3x Flow Control
HOL Blocking Prevention
- Port Mirroring: One-to-One
Many-to-One
Supports Mirroring for Tx/Rx/Both
- Multicast Filtering:
Forwards all unregistered groups
Filters all unregistered groups
- Configurable MDI/MDIX:
MLD snooping v1/v2 (256 groups)

VLAN

- 802.1Q
- VLAN Group
Max. 256 static VLAN groups
- Configurable VID from 1 - 4094
- Asymmetric VLAN
- Auto Voice VLAN
Max. 10 user-defined OUI
Max. 8 default OUI
- Auto Surveillance VLAN

Calidad de servicios (QoS)

- 802.1p Quality of Service
- 8 queues per port
- Queue Handling
Strict
Weighted Round Robin (WRR)
- Bandwidth Control
Port-based (Ingress/Egress, min granularity 10/100/1000 is 64 Kbps)
- QoS based on:
802.1p Priority Queues
DSCP
ToS
IPv6 Traffic Class
TCP/UDP port

Funcionalidades L3

- IP Interface
Supports 1 interface
- IPv6 Neighbor Discovery (ND)

Lista de control de acceso (ACL)

- Max. 50 access list
- Max. 768 rules shared by IPv4, MAC and IPv6
- Each rule can only be associated with a single port
- ACL based on
802.1p priority
VLAN
MAC address
- Ether type
- IP address
- DSCP
- Protocol type
- TCP/UDP port number
- IPv6 Traffic Class

Seguridad

- Broadcast/Multicast/Unicast Storm Control
- D-Link Safeguard Engine
- DHCP Server Screening

- IP-MAC-Port Binding (Smart Binding)
 - Supports 512 address binding entries
 - ARP Inspection
 - ARP + IP Inspection
 - Supports DHCP Snooping
- 802.1X Port-based Access Control
- ARP Spoofing Prevention
 - Max. 64 entries
- Traffic Segmentation
- SSH v2
- SSL
 - Supports v1/v2/v3
- Port Security
 - Supports up to 64 MAC addresses per port
- Duplicate address detection

AAA

- 802.1X Authentication
 - Supports local/RADIUS database
 - Supports port-based access control
 - Supports EAP, OTP, TLS, TTLS, PEAP
- IPv6 RADIUS Server
- Support MD5 authentication

Gestión

- Web-based GUI
- D-Link Network Assistant Utility
- Compact CLI
- Telnet Server
- TFTP Client
- Configurable MDI/MDIX
- SNMP
 - Supports v1/v2c/v3
- SNMP Trap
- Backup/Upgrade firmware
- Smart Wizard
- Upload/Download Configuration file
- System Log
 - Max. 500 log entries
- BootP/DHCP Client
- SNTP
- ICMP v6
- IPv4/v6 Dual Stack
- DHCP Auto Configuration
- Time Setting
 - SNTP
- RMONv1
- Trusted Host
- Consumo (Standby/Max.): 46.50W / 270.2W (PoE)
- Alimentación: 10 a 240 VAC, 50/60HZ fuente de alimentación interna
- Dimensiones (An x Prof x Alt): 440 x 430 x 44 mm
- Peso: 5.66 kg
- Ventilación: Ventiladores inteligentes

Físicas

Fecha Revisión

29-06-2016 por MSB

Comentarios

Aún no hay comentarios para este producto.