

Switch D-Link DGS-1100-24 24 p 10 / 100 / 1000 Mbps



Si eres un apasionado de la informática y la electrónica, te gusta estar a la última en tecnología y no perderte detalle, compra Switch D-Link DGS-1100-24 24 p 10 / 100 / 1000 Mbps al mejor...

Calificación: Sin calificación

Precio
Precio con descuento157,44 €

Precio de venta190,50 €

Precio de venta sin impuestos157,44 €

24 h
★★★★★

[Haga una pregunta sobre este producto](#)

Descripción Si eres un apasionado de la **informática y la electrónica**, te gusta estar a la última en tecnología y no perderte detalle, compra **Switch D-Link DGS-1100-24 24 p 10 / 100 / 1000 Mbps** al mejor precio.

Marca	D-Link
Modelo	DGS-1100-24
Especificaciones	- 24 puertos 10/100/1000 Mbps Standards - IEEE 802.3 compliant - IEEE 802.3u compliant - IEEE 802.3ab compliant - Supports Half/Full duplex operation at 10/100Mbps - Supports Full duplex operation at 1000Mbps - Supports Auto Negotiation for each port - Auto MDI/MDIX - IEEE 802.3x Flow Control support - IEEE 802.3az compliant Rendimiento: 48Gbps - Max.velocidad envío 35.71 Mpps - Tamaño tabla MAC 8K Entries - Packet Buffer 3.5Mbits

- Modo envío:
 - Store and Forward
- **Alimentación:**
 - 100 to 240 VAC, 50 to 60 Hz
- Max.Consumo
 - 14.83 Watts (DGS-1100-08)
- Consumo Standby
 - 6.49 Watts (DGS-1100-08)
- Sin ventilador
- Nivel acústico:
 - 0 dBA
- Dimensions (W x D x H)
 - 280mm x 180mm x 44 mm
- Peso:
 - 1.6kg
- LEDs
 - Power (Per Device)
 - PoE Max. (DGS-1100-08P Only)
 - Link/Activity/Speed (Per Port)
- Certifications
 - FCC Class A
 - CE Class A
 - VCCI Class A
- Verificaciones
 - UL/cUL
 - CE LVD
- MTBF
 - 774,990 Hours (DGS-1100-08)
- **VLAN**
 - Port-based VLAN
 - 802.1Q Tagged VLAN
 - Surveillance VLAN
 - Voice VLAN
 - Management VLAN
 - VLAN Group
 - Soporta 32 static VLAN groups
 - Max. 4094 VIDs
- **Funciones L2**
 - Flow Control
 - 802.3x Flow Control
 - HOL Blocking Prevention
 - IGMP Snooping
 - IGMP v1/v2 Snooping
 - Soporta 32 Groups
 - Loopback Detection
 - Link Aggregation
 - 8 groups, 2-4 ports per group (DGS-1100-16/24)
 - Port Mirroring
 - One-to-One
 - Many-to-One (DGS-1100-16/24 only)
 - Cable Diagnostics
 - Statistics
 - Tx Ok
 - Tx Error
 - Rx Ok
 - Rx Error
- **QoS**
 - 802.1p Quality of Service
 - 4 queues per port
 - Queue Handling
 - Strict
 - Weighted Round Robin (WRR)
- **Bandwidth Control**
 - DGS-1100-05/08/08P Port Based (Ingress/Egress, min. granularity 8 kb/s)
- **Seguridad**
 - Static MAC Address
 - Max. 128 entries
 - Broadcast/Multicast/Unknown Unicast Storm Control
- **Gestión**

Web-Based GUI (Soporta IPv4)
 Smart Console Utility
 - **D-Link Green**
 Power Saving by
 Link Status
 Cable Length
 Energy Efficient Ethernet (IEEE 802.3az)
 RoHS Compliant
 - **RFC Standard List**
 RFC 768 UDP
 RFC 791 IP
 RFC 792 ICMP
 RFC 793 TCP
 RFC 826 ARP
 RFC 951 BootP Client
 RFC 1542 BootP/DHCP client
 RFC 1945 HTTP/1.0
 RFC 2647 802.1p

Fecha de revisión

03-04-2014 por FE4

- Marca: D-Link
- Modelo: DGS-1100-24
- Especificaciones:
 - 24 puertos 10/100/1000 Mbps Standards
 - IEEE 802.3 compliant
 - IEEE 802.3u compliant
 - IEEE 802.3ab compliance
 - Soporta Half/Full-duplex operation at 10/100Mbps
 - Soporta Full-duplex operation at 1000Mbps
 - Soporta Auto-Negotiation for each port
 - Auto MDI/MDIX
 - IEEE 802.3x Flow Control support
 - IEEE 802.3az compliant Rendimiento: 48Gbps
 - Max.velocidad envío 35.71 Mpps
 - Tamaño tabla MAC 8K Entries
 - Packet Buffer 3.5Mbits
 - Modo envío: Store and Forward
 - Alimentación: 100 to 240 VAC, 50 to 60 Hz
 - Max.Consumo 14.83 Watts (DGS-1100-08)
 - Consumo Standby 6.49 Watts (DGS-1100-08)
 - Sin ventilador
 - Nivel acústico: 0 dBA
 - Dimensions (W x D x H) 280mm x 180mm x 44 mm
 - Peso: 1.6kg
 - LEDs Power (Per Device) PoE Max. (DGS-1100-08P Only) Link/Activity/Speed (Per Port)
 - Certifications FCC Class A CE Class A VCCI Class A
 - Verificaciones UL/cUL CE LVD
 - MTBF 774,990 Hours (DGS-1100-08)
 - VLAN Port-based VLAN 802.1Q Tagged VLAN Surveillance VLAN Voice VLAN Management VLAN VLAN Group Soporta 32 static VLAN groups Max. 4094 VIDs
 - Funciones L2 Flow Control 802.3x Flow Control HOL Blocking Prevention IGMP Snooping IGMP v1/v2 Snooping Soporta 32 Groups Loopback Detection Link Aggregation 8 groups, 2-4 ports per group (DGS-1100-16/24) Port Mirroring One-to-One Many-to-One (DGS-1100-16/24 only) Cable Diagnostics Statistics Tx Ok Tx Error Rx Ok
 - Rx Error
 - QoS 802.1p Quality of Service 4 queues per port Queue Handling Strict Weighted Round Robin (WRR)
 - Bandwidth Control
 - DGS-1100-05/08/08P Port Based (Ingress/Egress, min. granularity 8 kb/s)
 - Seguridad Static MAC Address Max. 128 entries Broadcast/Multicast/Unknown Unicast Storm Control
 - Gestión Web-Based GUI (Soporta IPv4) Smart Console Utility
 - D-Link Green Power Saving by Link Status Cable Length Energy Efficient Ethernet (IEEE 802.3az) RoHS Compliant
 - RFC Standard List RFC 768 UDP RFC 791 IP RFC 792 ICMP RFC 793 TCP RFC 826 ARP RFC 951 BootP Client RFC 1542 BootP/DHCP client RFC 1945 HTTP/1.0 RFC 2647 802.1p
- Fecha de revisión: 03-04-2014 por FE4

Comentarios

Aún no hay comentarios para este producto.