

Switch de Sobremesa D-Link EasySmart DGS-1100-08 8 Puertos RJ45 16 Gbit/s 1 Gbit/s Negro



Si eres un apasionado de la informática y la electrónica, te gusta estar a la última en tecnología y no perderte detalle, compra Switch de Sobremesa D-Link EasySmart DGS-1100-08 8 Puertos RJ45 16...

Calificación: Sin calificación

Precio

Precio con descuento41,15 €

Precio de venta49,79 €

Precio de venta sin impuestos41,15 €

24 h
★★★★★

[Haga una pregunta sobre este producto](#)

Descripción Si eres un apasionado de la **informática y la electrónica**, te gusta estar a la última en tecnología y no perderte detalle, compra **Switch de Sobremesa D-Link EasySmart DGS-1100-08 8 Puertos RJ45 16 Gbit/s 1 Gbit/s Negro** al mejor precio.

Marca	D-Link
Modelo	DGS-1100-08
Especificaciones	- 8 puertos 10/100/1000 Mbps Standards - IEEE 802.3 compliant - IEEE 802.3u compliant - IEEE 802.3ab compliance - Supports Half-Full-duplex operation at 10/100Mbps - Supports Full-duplex operation at 1000Mbps - Supports Auto-Negotiation for each port - Auto MDI/MDIX - IEEE 802.3x Flow Control support - IEEE 802.3az compliant Rendimiento: 16Gbps - Max.velocidad envío 11.9 Mpps

- Tamaño tabla MAC
8K Entries
- Packet Buffer
2Mbits
- Modo envío:
Store and Forward
- **Alimentación:**
100 to 240 VAC, 50 to 60 Hz
- Max.Consumo
4.89 Watts (DGS-1100-08)
- Consumo Standby
1.23 Watts (DGS-1100-08)
- Sin ventilador
- Nivel acústico:
0 dBA
- Dimensions (W x D x H)
171mm x 98 mm x 28mm
- Peso:
0.42kg
- LEDs
Power (Per Device)
PoE Max. (DGS-1100-08P Only)
Link/Activity/Speed (Per Port)
- Certifications
FCC Class A
CE Class A
VCCI Class A
- Verificaciones
UL/cUL
CE LVD
- MTBF
503,585 Hours (DGS-1100-08)
- **VLAN**
Port-based VLAN
802.1Q Tagged VLAN
Surveillance VLAN
Voice VLAN
Management VLAN
VLAN Group
Soporta 32 static VLAN groups
Max. 4094 VIDs
- **Funciones L2**
Flow Control
802.3x Flow Control
HOL Blocking Prevention
IGMP Snooping
IGMP v1/v2 Snooping
Soporta 32 Groups
Loopback Detection
Link Aggregation
2 groups, 2-4 ports per group (DGS-1100-08/08P)
Port Mirroring
One-to-One
Many-to-One (DGS-1100-16/24 only)
Cable Diagnostics
Statistics
Tx Ok
Tx Error
Rx Ok
Rx Error
- **QoS**
802.1p Quality of Service
4 queues per port
Queue Handling
Strict
Weighted Round Robin (WRR)
- **Bandwidth Control**
- DGS-1100-05/08/08P Port Based (Ingress/Egress, min. granularity 8 kb/s)
- **Seguridad**

	Static MAC Address
	Max. 32 entries (DGS-1100-05/08/08P)
	Broadcast/Multicast/Unknown Unicast Storm Control
	- Gestión
	Web-Based GUI (Soporta IPv4)
	Smart Console Utility
	- D-Link Green
	Power Saving by
	Link Status
	Cable Length
	Energy Efficient Ethernet (IEEE 802.3az)
	RoHS Compliant
	- RFC Standard List
	RFC 768 UDP
	RFC 791 IP
	RFC 792 ICMP
	RFC 793 TCP
	RFC 826 ARP
	RFC 951 BootP Client
	RFC 1542 BootP/DHCP client
	RFC 1945 HTTP/1.0
	RFC 2647 802.1p

Fecha de revisión

03-04-2014 por FEA

Comentarios

Aún no hay comentarios para este producto.